

# USB Flash

## Module and Drive (UFM/UFD)

### Compact, Easy-to-Integrate Embedded Storage

With their high-performance, high reliability and low cost-per-megabyte, HGST USB flash products meet the design requirements of embedded devices, including industrial PCs, point-of-sale (POS) terminals, networking equipment and automotive diagnostic applications.

HGST USB Flash Modules (UFMs) are plug-and-play USB 2.0 embedded storage solutions that simplify design and speed time-to-market. The 10-pin connector is a common interface found on many embedded system boards, and the standard mounting hole makes it easy to secure the module for rugged applications.

HGST USB Flash Drives (UFDs) are removable thumb drives with a high electrostatic discharge (ESD)-rated enclosure for applications that require Network Equipment-Building System (NEBS) Level 3 compliance. The standard USB 2.0 Series A interface provides designers with the flexibility of a true plug-and-play portable embedded storage device.

### Fast, Reliable and Cost-Effective

The USB standard is one of the simplest and most widely used protocols for embedded applications. Its widespread support, combined with its small size and low power, makes it an ideal boot device, code storage, or data logging solution where space, power and cost are key design considerations.

### Features and Benefits

Feature / Function	Benefits
High Performance	Up to 33MB/s sustained read and up to 26MB/s sustained write
Rugged Design	UFM: High tolerance to shock, vibration, altitude and temperature protects against mechanical failures UFD: Rugged ESD rated enclosure (tested for immunity from 8kV contact and 15kV air) protects against mechanical failures as a result of electrostatic discharge
Full data-path protection	Enhanced data integrity with full data-path protection and built in ECC engine that corrects up to 12 bits/512-Byte errors.
High endurance	Advanced wear-leveling and block management with guaranteed 2M program/erase cycles
Simple integration	USB 2.0 compliant. Plug-and-play for fast time-to-market
Physical interface	UFM: Choice of standard 2x5 pin (2.54mm height) or low-profile (2mm) 9-pin connector for integration flexibility UFD: Standard series A connector



## A True Enterprise-Class SSD for the Embedded Market

MACH16 Slim SATA delivers the features required for enterprise computing and other mission-critical applications where down-time is not an option.

### Information and Technical Support

www.hgst.com (Main Web site)  
www.hgst.com/partners (Partner Web site)

### North America

support\_usa@hgst.com  
Toll free: 1 888 426-5214, Direct: 1 408 717-8087

### Asia Pacific

support\_ap@hgst.com / 65 6840 9595

### EMEA and UK

support\_uk@hgst.com / 44 20 7133 0032

### Germany

support\_uk@hgst.com / 49 6929 993601

### Program Support

Partners First Program channelpartners@hgst.com

## Specifications

	USB Flash Drive	USB Flash Module
<b>Interface</b>		
Capacity	1/2/4/8Gb SATA	1/2/4/8/16GB
Type	USB 2.0	USB 2.0
Form Factor	Thumb Drive	10-pin Module
<b>Performance</b>		
Transactional Performance (Read IOPS)	2,000	2,000
Transactional Performance (Write IOPS)	640	640
Average Response Time	<90ms	<90ms
Transfer Rate (Read)	33MB/s	33MB/s
Transfer Rate (Write)	26MB/s	26MB/s
MTBF	4 million hours	2 million hours
<b>Physical</b>		
Size (L x W x H)	66.1mm X 16.6mm X 7.0mm	38.0mm X 23.0mm X 10.2mm
Power	<160mA	<160mA
Power Supply	5V or 3.3V	5V or 3.3V
<b>Environmental</b>		
Operational Temperature	-40°C to 85°C	-40°C to 85°C
Humidity (Non-Condensing)	85°C, 85% RH	85°C, 85% RH
Shock	1500G / 20G	1500G / 20G
Altitude	-1,000 to 85,000 ft	-1,000 to 85,000 ft
<b>Compliance</b>		
	RoHS-6, EU Directive	RoHS-6, EU Directive

<sup>1</sup> One GB is equal to one billion bytes when referring to hard drive capacity. Accessible capacity will vary depending on the operating environment and formatting.

<sup>2</sup> Portion of buffer capacity used for drive firmware

<sup>3</sup> MB is equal to MillionBytes

<sup>4</sup> Excludes command overhead

<sup>5</sup> MTBF target is based on a sample population and is estimated by statistical measurements and acceleration algorithms under median operating conditions. MTBF ratings are not intended to predict an individual drive's reliability. MTBF does not constitute a warranty.

© 2013 HGST, Inc., 3403 Yerba Buena Road, San Jose, CA 95135 USA. Produced in the United States 02/13. All rights reserved. Other trademarks are the property of their respective companies.

HGST trademarks are intended and authorized for use only in countries and jurisdictions in which HGST has obtained the rights to use, market and advertise the brand. Contact HGST for additional information. HGST shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks.

References in this publication to HGST's products, programs, or services do not imply that HGST intends to make these available in all countries in which it operates. Product specifications provided are sample specifications and do not constitute a warranty. Information is true as of the date of publication and is subject to change. Actual specifications for unique part numbers may vary.

Please visit the Support section of our website, [www.hgst.com/support](http://www.hgst.com/support), for additional information on product specifications. Photographs may show design models.

One GB is equal to one billion bytes and one TB equals 1,000 GB (one trillion bytes) when referring to hard drive capacity. Accessible capacity will vary from the stated capacity due to formatting and partitioning of the hard drive, the computer's operating system, and other factors.

MTBF target is based on a sample population and is estimated by statistical measurements and acceleration algorithms under median operating conditions. MTBF ratings are not intended to predict an individual drive's reliability. MTBF does not constitute a warranty.